



- NOTES:
1. COMPONENT TO BE MOLDED IN A CLEAR TRANSMISSIVE POLYCARBONATE.
  2. RECOMMENDED POSITION OF LED.

C		.06 WAS .04, .040 ± .007, (TYP) WAS .035 ± .007, (TYP) AND .118 (REF) WAS .118 ± .007.	MC	1-18-95
B		.06 ± .00-.01 WAS .06 & ADDED 45° X .015 CHAMFER TYP: (4) PLACES	MC	1-4-95
A				
LTR	EGR NO.			
REVISIONS		NEW RELEASE		
			App. J.	DATE
				N.O. 12-13-94
THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE PRIOR WRITTEN CONSENT OF DIALIGHT.				
SCALE	DRAWN	DATE	CUSTOMER DRAWING NO.	DWG. REV.
3:1	MC	12-12-94	C-15932	C
TOLERANCES, UNLESS OTHERWISE SPECIFIED:				
ALL DIM'S IN: INCHES				
FRACTIONS: ± 1/64				
DECIMALS(.XX) ± .01				
DECIMALS(.XXX) ± .005				
ANGLES: ± 1°				
FINISH:				
TITLE		LIGHTPIPE ARRAY		
PART NUMBER		515-1030		
DIALIGHT CORPORATION				
1913 Atlantic Ave.				
Manasquan, NJ 08736				
FSCM		83330		