

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION AUGUST, 2005.
 © COPYRIGHT 2005 By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
	C1	REVISED PER ECO-11-005033	01APR11	RK	HMR
	D	ECO-12-014680	20Aug2012	TITAN	MARTIN
	E	ECO-12-018113	27DEC2012	TITAN	MARTIN

NOTES:

1. SINGLE PACK IN ACCORDANCE WITH AMP SPEC 107-3275
2. 50 TRAY PACK IN ACCORDANCE WITH AMP SPEC 107-3275
3. Au PLATING OVER Ni PLATING OVER Cu PLATING
4. Ni PLATING OVER Cu PLATING
5. TIN PLATING
6. RECOMMENDED SELF-TAPPING SCREW 221108-4
7. RECOMMENDED MOUNT NUT 1-1634816-0
8. RECOMMENDED LOCKWASHER 1-1634817-0
9. FOR TECHNICAL DATA REFER TO YOUR LOCAL TE CONNECTIVITY SALES OFFICE
10. ALL DIMENSIONS ARE NOMINAL FOR REFERENCE ONLY UNLESS OTHERWISE STATED

BNC ELBOW PCB SOCKET 75 OHMS WITH MOUNTING POSTS
(1-1478031-0 & 6-1478031-0)

BNC ELBOW PCB SOCKET 75 OHMS WITH BOARD LOCKS
(1-1478031-1 & 6-1478031-1)

BNC ELBOW PCB SOCKET 75 OHMS WITHOUT MOUNTING POSTS
(1-1478031-2 & 6-1478031-2)

RECOMMENDED PCB LAYOUT WITH MOUNTING POSTS OR BOARD LOCKS

RECOMMENDED PCB LAYOUT WITHOUT MOUNTING POSTS

RECOMMENDED MOUNTING HOLE MAX PANEL THICKNESS: 5.5mm

Obsolete	Obsolete	Obsolete	Obsolete	Obsolete	Quantity	Material	Description	Item
1	1	1	1	1	1	ZINC DIECAST	BOARD LOCK	7
-	-	2	2	-	-	BRASS	MOUNTING POST	6
-	-	-	-	2	2	BRASS	SOLDER TAIL	5
1	1	1	1	1	1	BRASS	INSULATOR	4
1	1	1	1	1	1	PE-606	HOUSING	3
1	1	1	1	1	1	PBT WHITE	CONTACT	2
1	1	1	1	1	1	BRASS	CONTACT	1
6--2	1--2	6--1	1--1	6--0	1--0	MATERIAL	DESCRIPTION	ITEM

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	RITA ZUO	05 Mar 09
CHK	ANSON MA	05 Mar 09
APVD	BOB ZHAO	05 Mar 09

TE Connectivity

BNC LOW PROFILE R/A INSULATED PCB SOCKET 75 OHM WHITE

108-112000

SCALE: NTS SHEET: 1 OF 1 REV: E

1471-9 (3/11)