

Part Number: 6309UE



Security & Sound, #18-12c, BC, CMP

# **Product Description**

Security & Sound Cable, Plenum-CMP 12-18 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

# **Technical Specifications**

## **Physical Characteristics (Overall)**

Conduc	ctor		
AWG	Stranding	Material	No. of Conductors
18	7x26	BC - Bare Copper	12
Condu	ctor Count:		
Condu	ctor Size:		

#### Insulation

Material	Material Trade Name	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.008 in

### **Color Chart**



### **Outer Shield Material**



## **Outer Jacket Material**

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.287 in	0.015 in	Yes

## **Electrical Characteristics**

### Conductor DCR



## Capacitance

Nom. Capacitance Conductor to Conductor 32.5 pF/ft

Shielding: Unshielded

#### Current

Max. Recommended Current [A]

3.5 Amps per conductor @ 25°C A

#### Voltage

UL Voltage Rating 300 V RMS

#### **Temperature Range**

Operating Temp Range:	0°C To +75°C

## **Mechanical Characteristics**

Bulk Cable Weight:	83.9 lbs/1000ft
Max Recommended Pulling Tension:	268.8 lbs
Min Bend Radius/Minor Axis:	2.875 in

### **Standards**

	NEC/(UL) Specification:	CMP
ľ	CEC/C(UL) Specification:	CMP

## **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262 Plenum Flame Test (UL910)
CSA Flammability:	FT6
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	Yes

# **Part Number**

Non-Plenum Number:	5309UE

### Variants

Item #	Color	Footnote
6309UE 8771000	Natural	С
Footnote:		

### © 2018 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.